

ANPING MEGNKE
WIRE MESH MANUFACTURE CO., LTD



Concertina Razor Wire

CATALOG

Fencing System



info@walcoom.com



Concertina Razor Wire








Razor wire also called concertina razor wire, as an upgraded security products of traditional barbed wire, has enhanced level of security and safety. It can be used individually along the wall or the top of the buildings to form a certain obstacles against intruders. It is also popularly used along the top of the metal fences offering strengthened barriers with sharp blades and barbs. Razor wire is made by hot-dipped galvanized blade or stainless steel blade, high tensile strength core wire(steel wire with 1200mpa tensile strength or stainless steel wire).



⊕ Specifications of Razor wire

The Coil Diameter	No. of loops	Length Per Coil	Razor Wire Types	Notes
450 mm	33	7–8 m	CBT-60.65	single coil
500 mm	56	12–13 m	CBT-60.65	single coil
700 mm	56	13–14 m	CBT-60.65	single coil
960 mm	56	14–15 m	CBT-60.65	single coil
450 mm	56	8–9 m (3 clips)	BTO-10.12.18.22.28.30	cross type
500 mm	56	9–10 m (3 clips)	BTO-10.12.18.22.28.30	cross type
600 mm	56	10–11 m (3 clips)	BTO-10.12.18.22.28.30	cross type
600 mm	56	8–10 m (5 clips)	BTO-10.12.18.22.28.30	cross type
700 mm	56	8–10 m (5 clips)	BTO-10.12.18.22.28.30	cross type
800 mm	56	11–13 m (5 clips)	BTO-10.12.18.22.28.30	cross type
900 mm	56	12–14 m (5 clips)	BTO-10.12.18.22.28.30	cross type
960 mm	56	13–15 m (5 clips)	BTO-10.12.18.22.28.30	cross type

⊕ Razor wire type

Item	Blade Style	Thickness (mm)	Wire Dia. (mm)	Barb Length (mm)	Barb Width (mm)	Barb spacing (mm)
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1
BTO-18		0.5±0.05	2.5±0.1	18±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-28		0.5±0.05	2.5±0.1	28±1	15±1	45±1
BTO-30		0.5±0.05	2.5±0.1	30±1	18±1	45±1
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2



ANPING MENGKE

WIR EMESH MANUFACTURE CO., LTD



East Industrial Zone, Anping, Hebei,
China.



info@walcoom.com

